

Specifications: Engineered Douglas-fir Flooring



Product	Recycled Fir, FSC Mixed
Species	<i>Pseudotsuga menziesii</i>
Grain Pattern	Flat & vertical grain, knots and visible signs of distress.
Color Tones	Mainly amber with occasional tan/yellow sap streaking.
Product Description	<p>Our commitment to the environment shines with our FSC Recycled Douglas-fir flooring. Using beams from dismantled buildings and mature structures, a mix of grain patterns is achieved, each telling its own story. Whether working on a LEED project, or simply reducing your environmental footprint, recycled fir is a feel good choice. With a 4 mm wear layer this product maintains the distressed look of solid flooring with the versatility of an engineered product.</p> <p style="text-align: center;">*Current recycled stock is from laminated industrial beams, perpendicular glue lines are visible (can be cut out if desired), occasional aluminum nails may be found.</p>
Finish	UV Modified Oil. Finish is spot repairable.
Millwork	Engineered single-strip, micro-beveled edge, end-matched.
Dimensions	Standard dimensions: 5/8" thick X 5¼" face width X random solid lengths 12" to 48" Lengths up to 70" available upon request.
Wear Layer Thickness	4 mm
Density/Hardness	Hardness rating of 710 Janka (wear layer)
Core	FSC-Mixed multi-ply hardwood.
Packaging	Boxed, 22 ft ² /box.
Lead Time	6 to 8 weeks
Recommendations	Suitable for a wide variety of installations, including glue or float over concrete slab, below grade and/or over radiant heat. Install per NWFA guidelines.
Other	Available in unfinished square edged.
About These Specs	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.
Notes	* The product pictures represent the look of the floor and not the actual engineered flooring.



Contact Info

Address:

#5 10189 McDonald Pk. Rd.
Sidney, BC, V8L 3S8, Canada

Phone: 1-800-667-2275 , Fax: (250) 656 9663

Email: flooring@westwindhardwood.com

Web: <http://www.flooringbywestwindhardwood.com>