

Specifications: Solid Plank Douglas-fir Flooring



Product	Recycled Fir – Solid Plank, FSC Recycled
Species	<i>Pseudotsuga menziesii</i>
Grain Pattern	Flat & vertical, knots and visible signs of distress
Color Tones	Mainly amber with occasional tan/yellow sap streaking
Product Description	<p>Our commitment to the environment shines with our FSC Recycled Douglas-fir flooring. Using beams from dismantled buildings and mature structures, a mix of grain patterns is achieved, each telling its own story. Whether working on a LEED project, or simply reducing your environmental footprint, recycled fir is a feel good choice.</p> <p>*Current recycled stock is from laminated industrial beams, perpendicular glue lines are visible (can be cut out if desired), occasional aluminum nails may be found.</p>
Finish	Unfinished.
Millwork	Square edge, unmatched ends.
Dimensions	Standard dimensions: 3/4" thick X 4 1/4" face width X random lengths 4' to 10' Non standard dimensions available upon request.
Density/Hardness	Hardness rating of 710 Janka
Packaging	Bulk lift.
Lead Time	2 to 4 weeks
Recommendations	Nail down into subfloor or on stringers. Not recommended for installation on concrete or above radiant floors. Use our engineered flooring. Install per NWFA guidelines.
Other	Custom sizes available 1/2" to 2" thick, 2" to 7 1/4" wide.
About These Specs	This specification sheet is designed to give general information about our products. The specifications are subject to change and products are limited to material availability. Please contact us directly for the availability of this product and the particular specifications needed for your project. Detailed specifications will be confirmed in writing.
Contact Info	<p>Address: #5 10189 McDonald Pk. Rd. Sidney, BC, V8L 3S8, Canada</p> <p>Phone: 1-800-667-2275 , Fax: (250) 656 9663</p> <p>Email: flooring@westwindhardwood.com</p> <p>Web: http://www.flooringbywestwindhardwood.com</p>

